

COPPERBOND EARTH ROD



COPPERBOND EARTH ROD

99.95% pure copper & Q235 low carbon steel

Tensile Strength > 570N/mm

To be Bent 180 degrees without Cracks

No tear when driven to the ground

Usage Life more than 50 years

Coating Thickness(mm):0.33 / 0.254 / 0.2 / 0.15 / 0.1 / 0.05 / 0.025

UNTHREADED TYPE

Rod Diameter mm	Length mm
12.7	1200
12.7	1500
12.7	1800
12.7	2400
12.7	3000
14.2	1200
14.2	1500
14.2	1800
14.2	2400
14.2	3000
17.2	1200
17.2	1500
17.2	1800
17.2	2400
17.2	3000
23.0	2400
23.0	3000

THREADED TYPE

Rod Diameter mm	Length mm	Thread Diameter mm
12.7	1200	9/16"
12.7	1500	9/16"
12.7	1800	9/16"
12.7	2400	9/16"
12.7	3000	9/16"
14.2	1200	5/8"
14.2	1500	5/8"
14.2	1800	5/8"
14.2	2400	5/8"
14.2	3000	5/8"
17.2	1200	3/4"
17.2	1500	3/4"
17.2	1800	3/4"
17.2	2400	3/4"
17.2	3000	3/4"
23.0	2400	1"
23.0	3000	1"